



Suction couplings with long hose fitting

Order no.	Coupling size STORZ	DIN no.	DN adapter pieces Ø mm	Inner spacing of cleats	Material ¹
2 D 19 AL	D		19	31	AL
2 D 19 MS	D		19	31	MS
2 DAL	D	14301	25	31	AL
2 DMS	D		25	31	MS
2 C 25 AL	C		25	66	AL
2 C 25 MS	C		25	66	MS
2 DSS	D		25	31	SS
2 C 32 AL	C		32	66	AL
2 C 32 MS	C		32	66	MS
2 C 38 AL	C		38	66	AL
2 C 38 MS	C		38	66	MS
2 C 38 SS	C		38	66	SS
2 C 45 AL	C		45	66	AL
2 C 45 MS	C		45	66	MS
2 CAL	C	14321	52	66	AL
2 CMS	C		52	66	MS
2 CSS	C		52	66	SS
2 C 60 AL	C		60	66	AL

Order no.	Coupling size STORZ	DIN no.	DN adapter pieces Ø mm	Inner spacing of cleats	Material ¹
2 B 65 AL	B		65	89	AL
2 B 65 MS	B		65	89	MS
2 B 65 SS	B		65	89	SS
2 BAL	B	14322	75	89	AL
2 BMS	B		75	89	MS
2 B 75 SS	B		75	89	SS
2 B 80 AL	B		80	89	AL
2 A 100 AL	A		100	133	AL
2 A 100 MS	A		100	133	MS
2 A 100 SS	A		100	133	SS
2 AAL	A	14323	110	133	AL
2 AMS	A		110	133	MS
2 ASS	A		110	133	SS
2125 AL	125		125	148	AL
2135 AL	135		135	159	AL
2150 AL	150		150	160 (3 cleats)	AL
2165 AL	165		150	188	AL

STORZ fire hose couplings

With gaskets made of NBR natural rubber; oil and petrol resistant, for stainless steel couplings made of FPM

¹ Materials: SS = stainless steel, MS = brass, AL = aluminium alloy.

Other materials on request

Technical specifications are subject to change without further notice.



Suction coupling with long hose fitting