



Couplings with hose fitting

Order no.	DN <sup>1</sup>	Seal <sup>2</sup>	Material <sup>3</sup>	Weight = kg
SKG 10	10	NBR	TG	0.15
SKG 13	13	NBR	TG	0.16
SKG 13 SS	13	NBR	SS	0.16
SKG 15	15	NBR	TG	0.16
SKG 19	19	NBR	TG	0.18
SKG 19 SS	19	NBR	SS	0.18
SKG 25	25	NBR	TG	0.21
SKG 25 SS	25	NBR	SS	0.21
SKM 13	13	MS	TG	0.22
SKM 15	15	MS	TG	0.23
SKM 19	19	MS	TG	0.23
SKM 25	25	MS	TG	0.24



Hose clamps  
DIN 20039 A

Order no.	Hose outside Ø mm	Seal <sup>2</sup>	Material <sup>3</sup>	Weight = kg
SL 29	22 - 29		TG	0.13
SL 34	28 - 34		TG	0.13
SL 40	32 - 40		TG	0.20
SL 49	39 - 49		TG	0.26
SL 60	48 - 60		TG	0.31
SL 76	60 - 76		TG	0.36
SL 94	77 - 94		TG	0.58




Couplings with hose fitting and annular security collar

Order no.	DN <sup>1</sup>	Seal <sup>2</sup>	Material <sup>3</sup>	Weight = kg
SKB 13	13	NBR	TG	0.16
SKB 19	19	NBR	TG	0.19
SKB 25	25	NBR	TG	0.22



Hose clamps  
DIN 20039 B with safety claw

Order no.	Hose outside Ø mm	Seal <sup>2</sup>	Material <sup>3</sup>	Weight = kg
SK 34	28 - 32		TG	0.24
SK 39	35 - 42		TG	0.28
SK 44	42 - 45		TG	0.36
SK 51	45 - 53		TG	0.37
SK 60	55 - 60		TG	0.44
SK 73	60 - 73		TG	0.65



Coupling with hose fittings



Hose clamp DIN 20039 A



Coupling with hose fitting and annular security collar



Hose clamp DIN 20039 B with safety claw

## Compressed air couplings

With double cams for extra security, claw distance 42 mm  
According to DIN 3489<sup>4</sup>

<sup>1</sup> DN inner diameter of hose in mm

<sup>2</sup> Material: NBR = nitrile rubber, MS = brass, FPM = fluororubber

<sup>3</sup> Materials: TG = malleable iron, SS = stainless steel 1.4408

<sup>4</sup> Couplings with brass gaskets not according to DIN 3489

Other materials on request

Technical specifications are subject to change without further notice.